

BEACONS

3000 Series Strobe



REPLACE (x) AND (xx) IN ORDER NUMBER FOR PERSONALIZED SELECTIONS

Product Number: **3 (xx)7(x)(x)(x)**

Watt Options: **1Ø = 10 Watt or 2Ø = 20 Watt**

Flash: **7 = Double and Quad** (included in product number)

Height Options: **L = Low, 4" Dome or H = High, 6" Dome**

Mounting Options: **C = Flat/Pipe or M = Magnetic**

LED Color/Dome Color Options: **● A = Amber LEDs/Amber Lens** **○ C = White LEDs/Clear Lens**

Features

- > Lens with UV inhibitor prevents sun fade
- > Rated to last 20,000+ hours
- > Advanced circuitry designed tolerate high vibration applications

accessories

Branch Guard and Dust Cover (Beacon not included)



Branch Guards (6" shown)

4" Height **#PESB41BG4**

6" Height **#PESB41BG6**



Dust Cover

6" Height **#E36ØDC6**

TECHNICAL SPECIFICATIONS

FLASH PATTERNS	2 flash patterns - double or quad (user selectable)
TECHNOLOGY	Xenon Helix Strobe Tube
INPUT VOLTAGE	10-30 Vdc
CURRENT DRAW	10 Watts: 1 Amp @ 12 Vdc, 0.5 Amps @ 24 Vdc or 20 Watts: 2 Amps @ 12 Vdc, 1 Amp @ 24 Vdc
OPERATING TEMPERATURE	-40° C to 50° C
DIMENSIONS	4" Dome with base: 4.75" (12 cm) H 6" Dome with base: 6.7" (17 cm) H x 6.3" (16 cm) base diameter
MOUNTING	Permanent or Magnetic mount (polycarbonate lens and black base)
CERTIFICATIONS	SAE J 1318 Class 2 certified
WARRANTY	Two-year (strobe tube, one-year)